



HDS-V2 HARD DRIVE SHEAR



While smashing, bending, punching and sanitizing may meet a minimum requirements for hard drive disposal, they do not in fact destroy! Complete and total hard drive destruction is what your clients expect and it what the HDS-V2 delivers.

The HDS-V2 slices through hard drives rendering their stored data unretrievable. It provides the destruction level your clients are demanding at a process rate greatly surpassing other technologies. Our Hard Drive Shear is hydraulically actuated and can be mounted in a truck for onsite destruction or at your plant with an accessory pack.

Whether you pursue large purges or single hard drive opportunities, the HDS-V2 is up to the challenge.

HDS-V2 Specifications

SPECIFICATIONS

Orientation	Vertical
Cutting Technology	Shear
HDS Drive	Hydraulic Cylinder
Hydraulic Flow Rate	18 gal/mi
Electric Power Requirement	12 volts
System Pressure	1500 PSI
Feed System	Auto Feed Chamber
Throughput	300 Drives per hour
Limited Warranty	6 Month Parts
Width	34.5"
Height	42"
Depth	18.5"
Blade Width	1"
Average Shred Size	1"

OPTIONS

- Kubota D902-E4B Diesel Engine
- Auxiliary Power Wet Kit



Shredfast, Inc. | PO Box 1180 Airway Heights, WA 99001
Toll Free: 1-800-299-8437 | Local: (509) 244-7076 | Fax: (509) 244-7073
shredfast.com